


# VIBRATING SCREED TORNADO E-BATT

www.enargroup.com



TORNADO E-BATT vibrating screed is an exceptional option when choosing to vibrate concrete. Enar guarantees an optimum level of concrete compaction regardless of the type of concrete being vibrated. This screed is powered by a battery, thus no cable is needed. Also, it produces a low noise level and no residue. The profiles used on the Tornado are resistant and glide comfortably across concrete due to its floatability.

## DESIGNED & MANUFACTURED IN EUROPE FOR QUALITY AND EFFICIENCY

Robust, easy to use and ergonomic are words more frequently used when describing the Tornado from Enar. The rubber handles conform to many regulations and also provide a reduced level of vibrations to the user by means of new VAS system: down 50%.



### + Comfortable to Manage Reliably simple.

The Enar Tornado has handles that are designed to reduce the vibrations to the users hands and include VAS system making it more comfortable when being used.

### + Light And easy to use.

This product is easily used by one person on a job site thanks to its size and weight. This also allows for better transportation of the product.



### + Eco friendly No residue.

Less impact on the environment because its motor is powered by a battery.



### + No Maintenance Required No spare parts.

The brushless motor makes no necessary any maintenance. There are no parts to replace due to wear.



### + Secure and Reliable No electric risk.

24V safety voltage and no power cable ensure user protection.



## TECHNICAL DATA

MODEL	MOTOR	POWER (W)	FREQUENCY (vib/min)	CENTRIFUGAL FORCE (N)	WEIGHT (Kg)
TORNADO E-BATT	External vibrator 24V	130	5.500	1750	14,5

VOLTAGE (V)	NOMINAL CAPACITY (Ah)	AUTONOMY
24	14,5	min. 1 h.

## PROFILES

LENGTH (m)	WEIGHT (Kg)
1.5	4.6
2	6.2
2.5	7.8
3	9.3
4	12.5

- › High resistance, aluminium profiles.
- › Rounded ends to the profiles.
- › Strict flatness control while in use.
- › Profile base of 200mm/20cm to obtain a greater control and glide.
- › Profiles available from 1.5m to 4m .

