


EPS333TDE

Article code: 991013313



Europower super-silenced generating sets with Kubota water-cooled diesel engines, 3000rpm, 50Hz, 4 stroke

Generator:

kVA max.:	33
kVA cont.:	29
kVA:	9.7kVA @ 1~230V 29kVA @ 3~400V
Amps cont.:	42A @ 1~230V 42A @ 3~400V
Dimensions l x w x h:	170x74x118cm
Weight incl. oil (+ coolant if water-cooled), excl. fuel:	710kg
Weight incl. oil (+ coolant if water-cooled) + fuel:	772kg

Engine:

Brand/Type:	Kubota V1505T E2B-EU-Z1
HP max.:	41
Power:	30kW max. (3000rpm), 4-cylinder Diesel, Water-cooled
Displacement:	1498cm ³
Consumption @75% load:	6.5 litres/hour
Tank:	73 litres
Autonomy @75% load:	11.2 hours
Noise level:	71dB(A)@7m = Lwa 96
EU Emission norm:	Non emission IIIa
Battery voltage:	12V
CO2 emission:	0 g/kWh

Alternator:

Brand/Type	Mecc Alte ECP28-3L/2 - brushless
Nominal voltage:	3~400V and 1~230V
Frequency:	50Hz
Protection degree:	IP23

At present all EU portable generators in the power range from 18 to 560kVA are required to meet Stage IIIA regulations. A portable generator is either a rental set or a unit that is moved more than twice a year. The EU does not regulate emissions from stationary diesel generators used for prime power, peak shaving or emergency standby power.

Version:

- 2 sockets 230V - 16A + 1 socket CEE 230V - 16A + 1 socket CEE 230V - 32A + 1 socket CEE 400V - 32A 5 p. + 1 socket CEE 400V - 63A 5 p.
- 3 Amperemeters
- Automatic voltage regulator
- Central lifting eye
- Deep Sea Electronics module DSE4520 up to 275kVA and DSE7420 as of 300kVA
- Earth leakage protection 30mA with earth pin and 4m earth cable
- Electric start, maintenance free battery included
- Emergency stop
- Fuel pump 12V
- High temperature security
- Hour counter
- Low oil pressure guard
- Magneto-Stop
- Mecc Alte alternator Total+ for tropical environment
- Mechanical fuel level meter
- Oil drain pump
- Thermal magnetic breaker
- Voltmeter

Powered by:



Your **EUROPOWER** dealer