

**NEW FOR 2021** 

# **ACD 137 MONOBLOCK**

PORTABLE AIR-CONDITIONER AND DEHUMIDIFIER

### AIR-CONDITIONER AND DEHUMIDIFIER

# ACD 137 MONOBLOCK - 24,000 BTU/H

An innovative new product that allows multiple usage of being an air-conditioner and a dehumidifier. This durable and portable unit is ideal for emergency and temporary cooling and drying solutions including tents, mobile hospitals, work spaces and retail premises.



**ACD 137**Patent pending

#### **Advantages**

- High capacity air-conditioning COLD AIR: 24,000 Btu/h (equal to 7.1kW with just 1.98kW electrical supply)
- High capacity dehumidifying DRY AIR: 130 I/day water collection with just 1.98kW electrical supply
- Ducting connections
- Powerful and quiet fans
- Compact and lightweight
- Easy to install
- Heavy-duty casters
- Ideal for emergency and temporary solutions quick deployment for tents and mobile hospitals
- Portable spot air-conditioning for a wide range of applications like workshops, data centers, offices, retail premises

#### Included in the box



Twin adjustable hoses



Fix connector for flex tube

#### **Optional accessories**



**Flex tube for cold air** Ø31cm, 3m, PVC **4515.572** 



Flex tube for cold air Ø31cm, 3m, insulated 4515.370



Thermostat TAC for cooling – 4250.318



Air inlet plenum Ø30cm – 4250.319



Flex tube for cold air Ø31cm, 7.6m, nylon - **4515.360** Flex tube for warm air Ø41cm, 7.6m, nylon - **4515.361** 

Specifications	Units	ACD 137 Air-conditioner Mode	ACD 137 Dryer Mode	
Cooling capacity (28°C/55% RH)	kW	7.1	-	
	Btu/h	24,000	-	
Drying capacity (30°C/80% RH)	l/24h	-	130	
Air flow	m³/h	1020/800	1020/800	
Operating temperature range	°C	10-42	10-42	
Nominal power supply (28°C/55%)	W	1980	1980	
Nominal current (28°C/55%)	Α	10	10	
Max. current	Α	14	14	
Power supply	V/Hz	220-240/1ph/50	220-240/1ph/50	
Sound level	dB(A)	55	55	
Refrigerant		R1234YF A2L	R1234YF A2L	
Hot air outlet	mm	400	400	
Cold air outlet (standard)	mm	2 x 135	2 x 135	
Cold air outlet (accessory)	mm	300	300	
Product size (I x w x h) with handle	mm	790 x 620 x 1326	790 x 620 x 1326	
Box size (I x w x h)	mm	580 x 700 x 1500	580 x 700 x 1500	
Weight	kg	98	98	

## AIR-CONDITIONER AND DEHUMIDIFIER

# ACD 137 MONOBLOCK - 24,000 BTU/H


ACD 137 is an innovative portable device with multiple use:

- Air-conditioner COLD AIR: 7.1kW. Electric supply just 1.98kW
- Air dehumidifier DRY AIR: 130 l/day water collection
- Fan AIR VENTILATION




The control panel allows to select three modes:

- Air-conditioner (cooling mode)
- Air dryer (drying mode)
- Air ventilation (fan mode)




Cold and hot air circulate on the same side of ACD 137. This solution increases the efficiency of the cooling.


### Thanks to its flexibility, the ACD 137 can be used in different situations



**SPOT COOLING.** Placed into a room the cold air is blown towards the target (for example an electronic device that needs cooling down) and the hot air is blown upwards.



**ROOM COOLING.** The ACD 137 is placed inside a room and the cold air is blown into the room with the hot air ducted outside.



**ROOM COOLING.** The ACD 137 is placed outside a small room. The air is recirculated. The TAC room thermostat is placed inside the room to control the temperature.



**ROOM DRYING.** With the ACD 137 placed inside the room the dry air is blown around the room. The humidity removed from the air is collected into a tank.



Dantherm A/S

Marienlystvej 65 DK-7800 Skive Denmark t. +45 96 14 37 00

Dantherm Sp. z o.o.

ul. Magazynowa 5a 62-023 Gądki Poland t. +48 61 65 44 000

Dantherm SP S.A.

C/Calabozos 6 (Polígono Industrial) 28108 Alcobendas, Madrid Spain t. +34 91 661 45 00 Dantherm Ltd.

Unit 12, Galliford Road Maldon CM9 4XD United Kingdom t. +44 (0)1621 856611

Dantherm AS

Løkkeåsveien 26 3138 Skallestad Norway t. +47 33 35 16 00

Dantherm LLC

Transportnaya 22/2 142800, Stupino Moscow Russia t. +7 (495) 642 444 8 Dantherm GmbH

Oststraße 148 22844 Norderstedt Germany t. +49 40 526 8790

Dantherm AB

602 13 Norrköping Sweden

Dantherm SAS

23 rue Eugène Henaff 69694 Vénissieux Cedex France Dantherm S.p.A.

Via Gardesana 11 37010 Pastrengo (VR) Italy t. +39 045 6770533

Dantherm AG

Im Vorderasp 4 8154 Oberglatt ZH Switzerland t. +41 44 851 51 51

**MCS China** 

Unit 2B, No. 512 Yunchuan Road Baoshang, Shanghai, 201906 China t. +8621 61486668

Dealer:			

ebruary 202

